



UML/EX UML/EX/VT

Mulcher with fixed teeth rotor for excavators having a weight between 14 and 20 t.

Standard equipment: 63 cc hydraulic piston motor, anticavitation valve, flow control system valve, hydraulic hood.

110/60 cc variable torque hydraulic motor for the **UML/EX/VT**.

Options: custom made attachment plate with pins, diverter valve, possibility to have the rotor equipped with tooth type "C/3/HD", type K, blade C/3 or type I.



UML/EX

Model	Requirements			Excavator weight t. Min - Max	Working width mm	Weight Kg	Grinding diameter mm (max)	Teeth q.ty/type C/3+C/3/SS	Teeth q.ty/type I+C/3/SS
	Power HP Min - Max	Flow L/min Min - Max	Pressure Bar Min - Max						
UML/EX 100	90 - 120	110 - 150	220 - 350	14 - 20	1100	980	200	20+2	28+2
UML/EX 125	90 - 120	110 - 150	220 - 350	14 - 20	1340	1085	200	26+2	36+2
UML/EX 150	100 - 120	110 - 150	220 - 350	14 - 20	1580	1185	200	32+2	42+2

UML/EX/VT Hydraulic motor with variable torque

Model	Requirements			Excavator weight t. Min - Max	Working width mm	Weight Kg	Grinding diameter mm (max)	Teeth q.ty/type C/3+C/3/SS	Teeth q.ty/type I+C/3/SS
	Power HP Min - Max	Flow L/min Min - Max	Pressure Bar Min - Max						
UML/EX/VT 100	90 - 120	120 - 180	220 - 350	14 - 20	1100	980	200	20+2	28+2
UML/EX/VT 125	90 - 120	120 - 180	220 - 350	14 - 20	1340	1140	200	26+2	36+2
UML/EX/VT 150	100 - 120	120 - 180	220 - 350	14 - 20	1580	1240	200	32+2	42+2

Data refers to the machine without options.



Tooth type C/3
(standard)



Tooth type C/3/HD
(option)



Tooth blade type C/3
(option)



Tooth type K
(option)



Tooth type I
(option)



Tooth type C/3/SS
(side scraper)

The technical data are indicative, not binding and are subject to modification without prior notice.