



RC

Rock grinders with fixed teeth for excavators having a weight between 2.5 and 70 t.

Standard equipment: caged frame with built-in pre-drilled attachment flat plate, hydraulic block with flow control and check valve, motor safety cover, on-board oil filters, direct drive piston motor with automatic lubrication system that requires no daily maintenance, anti-wear plates on drum support, drum with replaceable heavy duty rock teeth.

Options: custom made attachment plate with pins.



RC

Model	Power HP	Requirements		Excavator weight t.	Working width mm	Weight Kg	Rotor diameter mm (STD)	Height w/out bracket mm
	Min - Max	Flow L/min Min - Max	Pressure Bar Min - Max					
RC 25	30 - 50	45 - 80	150 - 350	2,5 - 7	565	300	380	770
RC 45	50 - 100	65 - 120	180 - 350	6 - 14	625	470	450	900
RC 65	65 - 120	90 - 150	180 - 350	9 - 16	700	640	500	960
RC 90	90 - 140	130 - 190	220 - 350	14 - 22	800	1140	595	1250
RC 120	140 - 200	170 - 250	240 - 350	20 - 34	850	1465	660	1310
RC 220	200 - 380	240 - 340	240 - 380	28 - 45	950	2410	750	1575
RC 260	200 - 400	280 - 400	250 - 380	35 - 55	1000	2700	750	1675
RC 320	380 - 480	350 - 500	250 - 380	45 - 70	1250	3650	750	1770

Data refers to the machine without options.



Tooth type R/HD 65



Tooth type R 44