



DML/HY DML/HY/VT

Mulcher with fixed teeth for excavators having a weight between 5 and 13 t.

Standard equipment: variable displacement hydraulic piston motor (17-34 cc) with relief and anticavitation valve, flow control system valve, double protection hood with mechanical adjustment, rotor with tools type E and blade type E/HD.

For the **DML/HY/VT** 55/38 cc variable torque hydraulic motor.

Options: custom made attachment plate with pins, variable displacement hydraulic piston motor (32-65cc), hydraulic cylinders for the front and rear protection hood, diverter valve kit "Plug and Play".



DML/HY

Model	Power HP	Requirements		Excavators weight t.	Working width mm	Weight Kg	Grinding diameter mm (max)	Tooth q.ty Blade E
	Min - Max	Flow L/min Min - Max	Pressure Bar Min - Max					
DML/HY 100	50 - 100	50 - 130	180 - 250	5 - 13	1000	490	120	24
DML/HY 125	50 - 100	50 - 130	180 - 250	5 - 13	1240	510	120	30

DML/HY/VT Hydraulic motor with variable torque

Model	Power HP	Requirements		Excavators weight t.	Working width mm	Weight Kg	Grinding diameter mm (max)	Tooth q.ty Blade E
	Min - Max	Flow L/min Min - Max	Pressure Bar Min - Max					
DML/HY/VT 100	50 - 100	90 - 115	180 - 250	5 - 13	1000	490	120	24
DML/HY/VT 125	50 - 100	90 - 115	180 - 250	5 - 13	1240	510	120	30

Data refers to the machine without options.



Blade E



Blade type E/HD