



RSL

Rock shredder and Stone crusher for tractors between 80 and 190 HP with a max working depth of 27 cm.

Standard equipment: PTO driveshaft with cam clutch, hydraulic adjustable skids, HARDOX® counter blades, inner bolted HARDOX® plates for a complete anti-wear protection, bolted grid on rear hood, forged tool holders made of heat treated steel, oversized rotor bearings, „double steel cage system“ machine shell (WELDOX® steel) to provide an effective protection against dust, structural steel outside and wear resistant steel inside, rear hydraulic protection/doing hood for a better regulation of the output material, bolted forged rotor axles, available with. One side gearbox transmission (540 rpm) or with double side gearbox transmission (and 1000 rpm PTO).

Options: hydraulic top link. Possibility to have the rotor equipped with tooth type “G/3”.

Notes: For the correct usage, a creeper gear transmission is recommended.



RSL

| Model | Tractor HP Min Max | PTO rpm | Working width mm | Overall width mm | Weight Kg | Working depth mm (max) | Teeth q.ty/type R + R/HD | Teeth q.ty/type G/3+STC/3/FP+H |
|---------|-----------------------|------------|---------------------|---------------------|--------------|---------------------------|-----------------------------|-----------------------------------|
| RSL 100 | 80 - 120 | 540 | 1000 | 1435 | 1600 | 150 - 270 | 58 + 16 | 34+2+4 |
| RSL 125 | 90 - 120 | 540 | 1240 | 1675 | 1800 | 150 - 270 | 82 + 16 | 44+2+4 |
| RSL 150 | 100 - 120 | 540 | 1480 | 1915 | 1960 | 150 - 270 | 98 + 16 | 54+2+4 |

RSL/DT

| Model | Tractor HP Min Max | PTO rpm | Working width mm | Overall width mm | Weight Kg | Working depth mm (max) | Teeth q.ty/type R + R/HD | Teeth q.ty/type G/3+STC/3/FP+H |
|------------|-----------------------|------------|---------------------|---------------------|--------------|---------------------------|-----------------------------|-----------------------------------|
| RSL/DT 175 | 120 - 190 | 1000 | 1720 | 2065 | 2350 | 150 - 270 | 122 + 16 | 66+2+4 |
| RSL/DT 200 | 130 - 190 | 1000 | 1960 | 2305 | 2500 | 150 - 270 | 138 + 16 | 76+2+4 |
| RSL/DT 225 | 140 - 190 | 1000 | 2200 | 2545 | 2650 | 150 - 270 | 154 + 16 | 86+2+4 |

Data refers to the machine without options.



Tooth type R 50A



Tooth type R/HD 50A (option)



Tooth type G/3 (option)



Tooth type STC/3/FP (side scraper)