



UMM/DT

Forestry mulcher with fixed teeth rotor for tractors between 140 and 240 HP.

Standard equipment: PTO driveshaft with cam clutch, gearbox with freewheel, self-ranging system of the PTO drive shaft gearbox type "Z", hydraulic rear hood, centralized greasing hub, adjustable skids, adjustable extended three point linkage, counter blades and inner plates screwed from outside.

Options: mechanic or hydraulic guard frame, available with extra ripper teeth, special skids to go underground, third line counter blades, W-style self-aligning device between gearbox and PTO, possibility to have the rotor equipped with tooth type C/3/HD, type K, blade C/3 or type I.

Notes: For the correct usage, creeper gear transmission and reversible driving console are recommended.



UMM/DT

Model	Tractor HP		PTO rpm	Working width mm	Overall width mm	Weight Kg	Grinding diameter mm (max)	Teeth q.ty/type	
	min	max						C/3+C/3/SS	I+C/3/SS
UMM/DT 200	100	240	1000	2070	2470	2180	300	42+2	58+2
UMM/DT 225	110	240	1000	2310	2710	2430	300	46+2	66+2
UMM/DT 250	120	240	1000	2550	2950	2500	300	52+2	74+2

Data refers to the machine without options.



Tooth type C/3 (standard)



Tooth type C/3/HD (option)



Tooth blade type C/3 (option)



Tooth type K (option)



Tooth type I (option)



Tooth type C/3/SS (side scraper)

The technical data are indicative, not binding and are subject to modification without prior notice.