



UMH MEGA

Forestry mulcher with fixed teeth rotor for tractors between 350 and 500 HP.

Standard equipment: PTO driveshaft, gearbox with oil cooling system, hydraulic rear hood, centralized greasing hub, hydraulic top link, self-ranging system of the PTO drive shaft gearbox type "Z", adjustable extended three point linkage, hydraulic clutch transmission, counter blades and inner plates screwed from outside.

Options: mechanic or hydraulic guard frame, available with extra ripper teeth, adjustable skids, W-style self-aligning device between gearbox and PTO, possibility to have the rotor equipped with type "A/3/HD".

Notes: For the correct usage, creeper gear transmission and reversible driving console are recommended.



UMH MEGA

Model	Tractor HP		PTO rpm	Working width mm	Overall width mm	Weight Kg	Grinding diameter mm (max)	Working depth mm (max)	Teeth q.ty type A/3+MH
	min	max							
UMH MEGA 225	350	500	1000	2320	2820	5970	500	250	96+2
UMH MEGA 250	350	500	1000	2560	3060	6320	500	250	106+2

Data refers to the machine without options.



Tooth type A/3



Tooth type A/3/HD (option)



Tooth type MH (side scraper)

The technical data are indicative, not binding and are subject to modification without prior notice.